



## System SET

Factory-made triple wall concentric insulated chimney system allowing the connection of combustion air and the smoke exhaust in a balanced flue operation.



### MATERIAL

Inner wall: AISI 304 (SET1) / AISI 316L (SET2)

Outer wall: Galvanised steel

### FINISHING

Bright annealed (BA)

RAL colours (check prices)

Optional outer wall in AISI 304: + 16%

### INSULATION

High density rigid rockwool insulation (120kg/m<sup>3</sup>)

### WALL THICKNESS (mm)

Inner wall: 0.4 - 0.5 mm (depending on the diameter)

Insulation: 25 mm

Outer wall: 0.4 mm - 0.5 mm (depending on the diameter)

### AVAILABLE DIAMETERS (mm)

Ø130/230 - Ø150/250 - Ø180/300 - Ø200/350 - Ø250/400 - Ø300/450

### CONNECTION

Male-female push fit connection secured by locking band included



### APPLICATIONS

- Room sealed wall hung boilers and water heaters (SET1)
- Condensing wall hung boilers (SET2).



### CHARACTERISTICS

- Working temperature up to 200°C
- Continuous TIG/LASER welding in all items
- Locking band INCLUDED (except terminals)
- Shared collective exhaust and individual air intake (non balanced flue operation)
- Up to 10 boilers connected on maximal 5 levels
- External installation or in shared technical shafts
- T-caps, terminals, supports and brackets in Stainless steel
- Condensing seal joint included in the SEE 2

### CE MARK NUMBER

0036 CPR 9174 035

### CE CLASSIFICATIONS (EN 1856-1)

T200 - N1 - W - Vm - L20040 - O(00)

T200 - N1 - W - V2 - L50040 - O(00)

T200 - P1 - W - Vm - L20040 - O(00)

T200 - P1 - W - V2 - L50040 - O(00)

## Check prices

Jeremias Commercial Department

**+44 (0) 1623 889219**  
**sales@jeremias.uk**

